



# Ductile Iron Fittings

Range of proven-performance ductile iron fittings, flanged, socket and spigot fitting configurations.



## Applications

Potable water and wastewater pipelines

Water reticulation and irrigation

Water supply maintenance

Subdivisions

Pump Stations

## Product Attributes

Bureau Veritas S Mark accredited

High strength construction

Plascoat coated

Installed above and below ground

## Approvals/Standards

Approved to AS/NZ 2280 standard

Coating complies with AS/NZS 4158 and 4020 (WSAA Product Appraisal 05/12)

## Quality

ISO 9001:2008 Quality Management Standard

Gillies proven-performance ductile iron fittings are designed to work in conjunction with common pipe materials and dimensions with flanged, socket and spigot fitting configurations.



**FIG. 1** Plascoat PPA 571 coating process

**Attributes**

Gillies Metaltech has a proven record of performance in the New Zealand market and is the only New Zealand manufacturer of ductile and cast iron fittings, valves, and hydrants. Gillies also manufacture a range of special purpose pumps for stormwater, mining and petrochemical applications as well as effluent pumps for the farming market.

While historically, Gillies products have been constructed to exact British standards, this has been supplemented by the achievement of Bureau Veritas S Mark accreditation.

**Design Specifications**

- Sizes up to DN600, including bends, tees, flanges, flange adaptors and tapers
- USJ fittings are suitable for operating pressure up to 35 bar
- Flanged fittings are suitable for operating pressure up to 16 bar as standard. Higher pressures available.
- Flanged fittings are drilled Table D as standard, with other flange drillings available upon request
- Maximum deflection in the socket is 3.5°
- Fittings are supplied with Plascoat PPA 571 coating for superior protection

**Tees**

Flanged, USJ,  
Spigot configurations

Size range:  
up to DN600



**FIG. 2** Flanged Tee

**Hydrant Tees**

Flanged, USJ,  
Spigot configurations

Size range:  
up to DN600



**FIG. 3** Flanged Hydrant Tee



**FIG. 4** Socket Hydrant Tee



**FIG. 5** Spigot Hydrant Tee

## Bends

Flanged, USJ,  
Spigot configurations

Size range: up to DN600

Angles: 11° 22° 45° 90°



FIG. 6 Bend USJ 11°



FIG. 7 Bend USJ 22°



FIG. 8 Bend USJ 45°



FIG. 9 Bend USJ 90°



FIG. 10 Bend Flange 11°



FIG. 11 Bend Flange 22°



FIG. 12 Bend Flange 90°

## Flange Adaptors

USJ, Spigot configurations

Size range: up to DN600



FIG. 13 Socket Flange Adaptor

## Flanges

Blank & tapped 2" BSP



FIG. 14 Flanges

## Tapers

Flanged, USJ,  
Spigot configurations

Size range: up to DN600



FIG. 15 Reducing Flanges

**DISCLAIMER** While every effort has been made to ensure that the information in this document is correct and accurate, users of Hygrade provided product or information within this document must make their own assessment of suitability for their particular application. Product dimensions are nominal only, and should be verified if critical to a particular installation. No warranty is either expressed, implied, or statutory made by Hygrade Products Ltd unless expressly stated in any sale and purchase agreement entered into between Hygrade and the user.